

**NYSID Item Number: D4809-000-0000**

Revised: 07/20/05

**Product Description:**

<b>Style</b>	Master Roll - <del>PERFORATED CENTER</del>
<b>Item Size (each)</b>	20" x 620' (roll diameter not to exceed 40")
<b>Color</b>	1-side Blue; middle core White
<b>Composition</b>	100% Polypropylene
<b>Structure</b>	A bonded bilaminate nonwoven mat wherein one side is a sorbent comprised of randomly oriented meltblown micro-fibers [2-10 micron diameters], and the other side is a coverstock of lint-resistant & abrasion resistant spunbond nonwoven comprised of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters].
<b>Technology</b>	Spunbond & Meltblown (2-ply construction)
<b>Absorbency</b>	<b>Hydrophobic + Oleophilic</b>
<b>Bonding</b>	Dimpled (staggered pattern) + Mechanical entanglement

<b>Intended Application</b>	Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or Solvent Base Liquids
-----------------------------	--

<b>Absorbency Capacity</b>	106 gal. per master roll (saturated; medium viscosity-12x)
----------------------------	--

**Packaging Description:**

Package configuration	1-Pallet/location	Roll Weight	64-lbs
Items per Package	4-Master Roll/location	Roll Dimensions	38"Diameter x 20"Height
Container type	Wrap or netting	Pallet caps	Top & Bottom

**Physical Properties:**

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002	G/M2	300	30
Caliper	SPCTM-003	mils	190	20
Absorbency** (med. Oil)	SPCTM-004B	gL/gS	12	2
Tensile Strength	SPCTM-006	lbs	15	2
Color	Visual	-----	Blue/White	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

<b>Attributes</b>	Product will be free of foreign material contamination, rips, holes, and tears.
<b>Packaging</b>	Roll not to exceed 40" diameter. Store/ship rolls flat and not warped.
<b>Labeling</b>	Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code) and Roll Weights.
<b>Certification</b>	Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery.