

**NYSID Item Number: D4819-000-0000**

Revised: 07/20/05

**Product Description:**

|                         |  |
|-------------------------|--|
| <b>Style</b>            | Master Roll  |
| <b>Item Size (each)</b> | 30" x 920' (roll diameter not to exceed 40")   |
| <b>Color</b>            | 1-side Blue; middle core White   |
| <b>Composition</b>      | 100% Polypropylene   |
| <b>Structure</b>        | A bonded bilaminate nonwoven mat wherein one side is a sorbent comprised of randomly oriented meltblown micro-fibers [2-10 micron diameters], and the other side is a coverstock of lint-resistant & abrasion resistant spunbond nonwoven comprised of continuous filaments randomly oriented and thermally point bonded [15-30 micron diameters]. |
| <b>Technology</b>       | Spunbond & Meltblown (2-ply construction)  |
| <b>Absorbency</b>       | <b>Hydrophobic + Oleophilic</b>  |
| <b>Bonding</b>          | Dimpled (staggered pattern) + Mechanical entanglement  |

|                             |  |
|-----------------------------|--|
| <b>Intended Application</b> | Abrasion Resistant, Lint Resistant, & Chemical Resistant Sorbent for Oil or Solvent Base Liquids |
|-----------------------------|--|

|                            |  |
|----------------------------|--|
| <b>Absorbency Capacity</b> | 235 gal. per master roll (saturated; medium viscosity-12x) |
|----------------------------|--|

**Packaging Description:**

|                       |                   |                 |                            |
|-----------------------|-------------------|-----------------|----------------------------|
| Package configuration | 1-Pallet/location | Roll Weight     | 141-lbs                    |
| Items per Package     | 3-Master          | Roll Dimensions | 40"Diameter x<br>30"Height |
|                       | Roll/location     |                 |                            |
| Container type        | Wrap or netting   | Pallet caps     | Top & Bottom               |

**Physical Properties:**

| Parameter               | SPC Test Method | Units | Nominal    | (+/-)Tolerance |
|-------------------------|-----------------|-------|------------|----------------|
| Basis Weight            | SPCTM-002       | G/M2  | 300        | 30             |
| Caliper                 | SPCTM-003       | mils  | 190        | 20             |
| Absorbency** (med. Oil) | SPCTM-004B      | gL/gS | 12         | 2              |
| Tensile Strength        | SPCTM-006       | lbs   | 15         | 2              |
| Color                   | Visual          | ----- | Blue/White | per standard   |

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped.

\*\* The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

|                      |  |
|----------------------|--|
| <b>Attributes</b>    | Product will be free of foreign material contamination, rips, holes, and tears.  |
| <b>Packaging</b>     | Roll not to exceed 40" diameter. Store/ship rolls flat and not warped.   |
| <b>Labeling</b>      | Each package to be clearly labeled with Company Name, Address, Item No., Date, and/or Package Code (Bar Code) and Roll Weights.                          |
| <b>Certification</b> | Make no changes in basic process or composition without notifying customer. Claims for non-conformance of goods must be made within 60-days of delivery. |